

OPTIMAL DESIGN OF THIN-WALLED LAMINATED BEAMS WITH GEOMETRICALLY NONLINEAR BEHAVIOUR

Aníbal J. Valido¹, João B. Cardoso², Paulo P. Moita³

¹ Escola Superior de Tecnologia de Setúbal, Instituto Politécnico de Setúbal, Campus do IPS, Estefanilha, 2914-508 Setúbal, Portugal

CENTEC-IST, Av. Rovisco Pais, 1, 1049-001 Lisboa, Portugal

anibal.valido@estsetubal.ips.pt

² IDMEC-IST, Av. Rovisco Pais, 1, 1049-001 Lisboa, Portugal, barradas@ist.utl.pt

³ Escola Superior de Tecnologia de Setúbal, Instituto Politécnico de Setúbal, Campus do IPS, Estefanilha, 2914-508 Setúbal, Portugal

CENTEC-IST, Instituto Superior Técnico, Lisboa, Portugal

paulo.moita@estsetubal.ips.pt

Key Words: *Thin-walled Beams, Composite Structures, Nonlinear Analysis, Optimal Design*

The purpose of this paper is to present a finite element model for optimal design of composite laminated thin-walled beam structures, with geometrically nonlinear behaviour, including post-critical behaviour and accounting warping deformation.

A general continuum formulation is presented for the structural nonlinear analysis, based on the virtual work principle, and using the Updated Lagrangean procedure to describe the deformation of the structure. In order of defining the post-critical behaviour, a generalized displacement control method has been implemented.

The thin-walled beam cross-section is considered as made from an assembly of flat layered laminated composite panels. The cross-section bending-torsion properties are integrals based on the cross-section geometry, on the warping function and on the individual stiffness of the laminates that constitute the cross-section.

In order to determine its bending-torsion properties, the cross-section geometry is discretized by quadratic isoparametric finite elements. Along its axial direction, the beam is modelled throughout two-node Hermitean finite elements with seven degrees-of-freedom a node.

Design sensitivities are imbedded into the finite element modelling and assembled in order to perform the design sensitivity analysis of various structural performance measures by using the adjoint method.

As design variables one considers laminate thickness, lamina orientations and the global cross-section geometry. This geometry is defined by the position of master nodes related to the cross-section finite element mesh.

Design optimization is performed throughout nonlinear programming techniques.

REFERENCES

- [1] V.Z. Vlasov, *Thin-walled Elastic Beams*, Israel Program for Scientific Translations, Jerusalem, 1961.
- [2] S. W. Tsai, *Theory of Composites Design*, Think Composites, 1992.
- [3] N. Bauld and L. Tzeng, A Vlasov theory for fiber-reinforced beams with thin-walled open cross sections, *International Journal Solids and Structures*, 20(3), 277-97, 1984.
- [4] Aníbal J. Valido and J. Barradas Cardoso, Geometrically Nonlinear Composite Beam Structures-Design Sensitivity Analysis, *Engineering Optimization*, 35 (5), 531-551, 2003.
- [5] Aníbal J. Valido and J. Barradas Cardoso, Geometrically Nonlinear Composite Beam Structures-Optimal Design, *Engineering Optimization*, 35 (5), 553-560, 2003.
- [6] J.E. Barradas Cardoso, Nuno M.B. Bedito and Aníbal J.J. Valido , Finite Element Analysis of Thin-Walled Composite Laminated Beams with Geometrically Nonlinear Behavior Including Warping Deformation, *Thin-Walled Structures*, 47, 1363-1372, 2009.
- [7] J. Barradas Cardoso and Aníbal J. Valido, Cross-section Optimal Design of Composite Laminated Thin-walled Beams, *Computers and Structures*, 89, 1069-1076, 2011.